

[Back to Search](#)[My Tools ▾](#)[Search History](#)[Marked List](#)[Full Text](#)[Save to EndNote online](#)[Add to Marked List](#)[Back to List](#)

1 of 1

Bidirectional flow micropump based on dynamic rectification

By: [Chee, PS](#) (Chee, Pei Song)^[1]; [Rahim, RA](#) (Rahim, Ruzairi Abdul)^[1]; [Arsat, R](#) (Arsat, Rashidah)^[1]; [Hashim, U](#) (Hashim, Uda)^[2]; [Leow, PL](#) (Leow, Pei Ling)^[1]

SENSORS AND ACTUATORS A-PHYSICAL

Volume: 204 Pages: 107-113

DOI: 10.1016/j.sna.2013.09.033

Published: DEC 15 2013

[View Journal Information](#)

Abstract

This paper proposes a new bidirectional pumping principle based on a dynamic rectification mechanism. The pump is composed of a moveable actuation platform and a gourd-shaped chamber, whose role is to behave as both a rectification and a pumping structure. An asymmetrically deflected membrane induces a differential pressure across the chamber and thus generates a pumping effect. The stream flow field inside the chamber was verified by numerical simulations. Furthermore, the feasibility of the pump was examined by developing a polydimethylsiloxane (PDMS)-based prototype using micro-electromechanical (MEMS) fabrication technology. Because the pumping performance is directional, the micropump characteristics were evaluated at different actuation points along the membrane. In addition, the operating performance was assessed over a range of low driving frequencies (1-10 Hz, in 1 Hz increments) and over a nominal frequency ranges (5-55 Hz, in 5 Hz increments). The proposed micropump exhibits maximum flow rates of 1.52 ml/min in the forward direction and 1.48 ml/min in the reverse direction, with resonance frequencies of 15 Hz and 20 Hz, respectively. The presented pump offers advantage in

Citation Network

0 Times Cited

[19 Cited References](#)

[View Related Records](#)

[View Citation Map](#)

[Create Citation Alert](#)

(data from Web of Science™ Core Collection)

All Times Cited Counts

0 in All Databases

0 in Web of Science Core Collection

0 in BIOSIS Citation Index

0 in Chinese Science Citation Database

0 in Data Citation Index

0 in SciELO Citation Index

future disposable microfluidics applications due to its bi-directional properties, low fabrication cost and modular architecture. (C) 2013 Elsevier B.V. All rights reserved.

Keywords

Author Keywords: [Bi-directional micropumps](#); [Dynamic structure valve](#); [Electromagnetic actuation](#); [Numerical simulation](#)

KeyWords Plus: [PIEZOELECTRIC MICROPUMP](#); [VALVELESS MICROPUMP](#); [DRUG-DELIVERY](#); [SYSTEM](#)

Author Information

Reprint Address: Leow, PL (reprint author)

+ UTM, Fac Elect Engn, Johor Baharu 81310, Johor, Malaysia.

Addresses:

+ [1] UTM, Fac Elect Engn, Johor Baharu 81310, Johor, Malaysia

+ [2] Univ Malaysia Perlis, Inst Nanoelect Engn, Kangar 01000, Perlis, Malaysia

E-mail Addresses: leowpl@fke.utm.my

Funding

Funding Agency	Grant Number
Ministry of Higher Education of Malaysia	
UTM-Research University Grant (GUP)	Q.J130000.2623.08J76

[View funding text](#)

Publisher

ELSEVIER SCIENCE SA, PO BOX 564, 1001 LAUSANNE, SWITZERLAND

Categories / Classification

Research Areas: [Engineering](#); [Instruments & Instrumentation](#)

Web of Science Categories: [Engineering, Electrical & Electronic](#); [Instruments & Instrumentation](#)

This record is from:
Web of Science™ Core Collection

Suggest a correction

If you would like to improve the quality of the data in this record, please [suggest a correction](#).

Document Information

Document Type: Article

Language: English

Accession Number: WOS:000328726600014

ISSN: 0924-4247

Journal Information

Impact Factor: [Journal Citation Reports®](#)

Other Information

IDS Number: 276CV

Cited References in Web of Science Core Collection: **19**

Times Cited in Web of Science Core Collection: **0**

[Back to List](#)

1 of 1